

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED): *Auto Butler Paint Sealant*
SYNONYMS: Paint Sealant
CAS#: Mixture
PRODUCT USE: Automotive Polish/Sealant
CHEMICAL SHIPPING NAME/CLASS: See Section 14 for Details
U.N. NUMBER: See Section 14 for Details
MANUFACTURER'S NAME: Broadway Equipment Company
ADDRESS: 4701 Humboldt Ave. N
Minneapolis, MN 55430
BUSINESS PHONE: 1-612-529-3345
EMERGENCY PHONE: 1-800- 328- 7434
DATE OF CURRENT REVISION: May 31, 2015
DATE OF LAST REVISION: March 25, 2014

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: This product is an opaque pink liquid with a solvent odor.
Health Hazards: Prolonged or repeated exposure may cause irritation to skin. May cause irritation to eyes upon contact. Inhalation of vapors/sprays or mist may cause respiratory irritation, drowsiness or dizziness. Ingestion of large amounts of this product may cause gastrointestinal irritation.
Flammability Hazards: This product is a combustible liquid with a flash point of >149°F (>62°C). Combustible liquids are defined as having a flash point between 100°F and 200°F.
Reactivity Hazards: None known.
Environmental Hazards: The Environmental effects of this product have not been investigated. Release of this product is not anticipated to have significant adverse effects in the aquatic environment.

US DOT SYMBOLS

See Section 14 for Details



CANADA (WHMIS) SYMBOLS



EUROPEAN and (GHS) HAZARD SYMBOLS

Signal Word: DANGER



EU LABELING AND CLASSIFICATION:

This product does meet the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED):	Auto Butler Paint Sealant
SYNONYMS:	Paint Sealant
CAS#:	Mixture
PRODUCT USE:	Automotive Polish/Sealant
CHEMICAL SHIPPING NAME/CLASS:	See Section 14 for Details
U.N. NUMBER:	See Section 14 for Details
MANUFACTURER'S NAME:	Broadway Equipment Company
ADDRESS:	4701 Humboldt Ave. N Minneapolis, MN 55430
BUSINESS PHONE:	1-612-529-3345
EMERGENCY PHONE:	1-800- 328- 7434
DATE OF CURRENT REVISION:	May 31, 2015
DATE OF LAST REVISION:	March 25, 2014

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:	This product is an opaque pink liquid with a solvent odor.
Health Hazards:	Prolonged or repeated exposure may cause irritation to skin. May cause irritation to eyes upon contact. Inhalation of vapors/sprays or mist may cause respiratory irritation, drowsiness or dizziness. Ingestion of large amounts of this product may cause gastrointestinal irritation.
Flammability Hazards:	This product is a combustible liquid with a flash point of >149°F (>62°C). Combustible liquids are defined as having a flash point between 100°F and 200°F.
Reactivity Hazards:	None known.
Environmental Hazards:	The Environmental effects of this product have not been investigated. Release of this product is not anticipated to have significant adverse effects in the aquatic environment.

US DOT SYMBOLS

See Section 14 for Details



CANADA (WHMIS) SYMBOLS



EUROPEAN and (GHS) HAZARD SYMBOLS

Signal Word: DANGER



EU LABELING AND CLASSIFICATION:

This product does meet the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

EU HAZARD CLASSIFICATION OF INGREDIENTS PER DIRECTIVE 1272/2008/EC:

Index Number:

EC# 231-791-2 This substance is not classified in the Annex I of Directive 67/548/EEC

EC# 266-340-9 This substance is not classified in the Annex VI of Directive 67/548/EEC

EC# 265-191-7 Annex VI Index# 649-405-00-X

Substances not listed either individually or in group entries must be self-classified.

Component(s) Contributing to Classification(s):

All Ingredients.

GHS Hazard Classification(s):

Flammable Liquid Category 4

Aspiration Toxicity Category 1

Skin Irritant Category 2B

Eye Irritant Category 2

STOT SE Category 1

Hazard Statement(s):

H227: Combustible liquid.

H304: May be fatal if swallowed and enters airway

H315: Causes skin irritation.

H320: Causes eye irritation.

H335: May cause respiratory irritation.

H372: Causes damage to organs through prolonged or repeated exposure

Precautionary Statement(s):

P260: Do not breathe dust/fume/vapor/mist/spray

P264: Wash thoroughly after handling.

P281: Use personal protective equipment as required.

P210: Keep away from heat/sparks/open flame/hot surfaces. — No Smoking

P270: Do not eat, drink or smoke when using this product.

EU HAZARD CLASSIFICATION OF INGREDIENTS PER DIRECTIVE 1999/45/EC:

[F] Flammable, [Xi] Irritant [Xn] Harmful

Risk Phrases:

R10: Flammable.

R36/37/38: Irritating to eyes respiratory system and skin

R67: Vapors may cause drowsiness or dizziness.

R22: Harmful if swallowed

Safety Phrases:

S16: Keep away from sources of ignition.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S39: Wear suitable eye/face protection.

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE:

The most significant routes of overexposure for this product are by contact with skin or eyes, inhalation of vapors and ingestion. The symptoms of overexposure are described below.

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

ACUTE:

INHALATION:

Inhalation of vapors/mist/spray may cause respiratory irritation.

CONTACT WITH SKIN:

Prolonged and repeated contact may cause irritation to skin.

EYE CONTACT:

Direct eye contact can cause irritation with redness, tearing and blurred vision.

INGESTION:

Ingestion may cause gastrointestinal irritation, nausea and vomiting. Caution Aspiration Hazard if swallowed and enters airways or if vomiting occurs and enters lungs.

CHRONIC:

Prolonged and repeated exposure to this product may cause damage to the central nervous system.

TARGET ORGANS:

ACUTE:

Skin, Respiratory System, and Eyes.

CHRONIC:

Respiratory System

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients:	WT%	CAS#	EINECS #	Hazard Classification	Risk Phrases
Water	60 - 70%	7732-18-5	231-791-2	None	None
Ceramic materials and wares	5 - 15%	66402-68-4	266-340-9	[Xi] Irritant	R36/38
Solvent Naphtha, Petroleum	10 - 20%	64742-88-7	265-191-7	[Xi] Irritant [Xn] Harmful	R22, R37
Balance of other ingredients is less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000.

4. FIRST-AID MEASURES

EYE CONTACT:

If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation persists.

SKIN CONTACT:

Wash skin thoroughly with soap and water after handling. Seek medical attention if irritation develops and persists.

INHALATION:

If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

INGESTION:

If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Individuals with pre-existing skin or respiratory problems may be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS:

Treat symptoms and eliminate overexposure.

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI; Canadian WHMIS Standards; Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

5. FIRE-FIGHTING MEASURES

FLASH POINT:

AUTOIGNITION TEMPERATURE:

FLAMMABLE LIMITS — IN AIR BY VOLUME, %:

FIRE EXTINGUISHING MATERIALS:

Water Spray: Yes

Carbon Dioxide:

Foam: Yes

Dry Chemical:

Halon: Yes

Other:

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Explosion Sensitivity to Mechanical Impact:

Explosion Sensitivity to Static Discharge:

SPECIAL FIRE-FIGHTING PROCEDURES:

Non-Flammable with flash point >149°F (>62.0°C)

Not Available

Lower N/A, Upper N/A

Use fire extinguishing methods below.

Yes

Yes

Any "C" Class


Not considered a fire or explosion hazard.

No

No

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM



HMIS RATING SYSTEM

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)			2
FLAMMABILITY HAZARD (RED)			2
PHYSICAL HAZARD (YELLOW)			0
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	See Sect 8		See Sect 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe 5 = Chronic Hazard

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Stop the flow of material, if this can be done safely. Eliminate sources of ignition. Contain discharged material. Absorb spill using an absorbent, non-combustible material such as earth, sand, or vermiculite. Place in a proper container for disposal. Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

7. HANDLING AND STORAGE

WORK PRACTICES AND HYGIENE PRACTICES:

As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Use good hygiene practices.

STORAGE AND HANDLING PRACTICES:

Store in original container. Keep container closed. Store in cool, dry, well ventilated area away from sources of ignition. Storage vessels should be grounded.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

Chemical Name	CAS#	ACGIH TLV	OSHA TWA
Water	7732-18-5	Not Listed	Not Listed
Solvent Naphtha Petroleum	64742-88-7	Not Listed	Not Listed

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart 1 (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Not normally required when using this product. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or goggles are recommended to avoid eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

HAND PROTECTION: Wear chemical resistant gloves to avoid skin contact when using this product. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards or relevant Japanese Standards.

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

BODY PROTECTION:

Use body protection appropriate to task being performed. If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

9. PHYSICAL and CHEMICAL PROPERTIES

APPEARANCE (Physical State) and

COLOR:

This product is a pink opaque Liquid.

ODOR:

Slight

ODOR THRESHOLD:

Not Applicable

pH:

Not Available

MELTING/FREEZING POINT:

Not Available

FLASH POINT:

212°F

EVAPORATION RATE (n-BuAc=1):

Not Available

FLAMMABILITY (SOLID, GAS):

Not Applicable

UPPER-LOWER FLAMMABLE OR

EXPLOSION LIMITS:

Not Applicable

VAPOR PRESSURE (mm Hg @

20°C)

Not Available

VAPOR DENSITY:

Not Available

RELATIVE DENSITY:

Not Available

SPECIFIC GRAVITY:

0.9768 (Typical)

SOLUBILITY IN WATER:

Soluble

WEIGHT PER GALLON:

8.2 pounds per gallon

PARTITION COEFFICIENT:

Not Available

AUTO-IGNITION TEMPERATURE:

Not Applicable

DECOMPOSITION TEMPERATURE:

Not Available

VISCOSITY:

Not Available

10. STABILITY and REACTIVITY

STABILITY:

Stable under conditions of normal storage and use.

HAZARDOUS DECOMPOSITION

PRODUCTS:

Thermal decomposition products include carbon dioxide and carbon monoxide.

MATERIALS WITH WHICH

SUBSTANCE IS INCOMPATIBLE:

Strong oxidizing materials.

POSSIBILITY OF HAZARDOUS

REACTIONS:

Will not occur.

CONDITIONS TO AVOID:

Incompatible materials.

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA:

No LD50 Data Available

SUSPECTED CANCER AGENT:

Ingredients with this product are not found on the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

**IRRITANCY OF PRODUCT:
SENSITIZATION TO THE
PRODUCT:
REPRODUCTIVE TOXICITY
INFORMATION:**

This product may be irritating to skin, eyes or respiratory system.

This product is not a skin and respiratory sensitizer.

No information concerning the effects of this product and its components on the human reproductive system.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY:

No specific data available on this product.

**CHEMICAL EFFECT ON PLANTS,
ANIMALS AND AQUATIC LIFE:**

This product is not expected to cause significant harm to plants, animals or aquatic life.

**WATER ENDANGERMENT CLASS:
SPECIFIC AVAILABLE COMPONENT
INFORMATION:**

Not water endangering in accordance with EU Guideline 91/155-EWG.

No additional data available at this time.

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State and local regulations, those of Canada, Australia, EU Member States and Japan.

EU WASTE CODE:

Not determined.

14. TRANSPORTATION INFORMATION

US DOT, IATA, IMO, ADR:

THIS PRODUCT IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

This product is classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

NOTE: Combustible liquids may be shipped as Limited Quantities if packaged as described in 49 CFR 173.150 (b) if the inner packaging is not over 5 L. The requirements of 49 CFR Subchapter C do not apply to any material classed as a combustible liquid in a non-bulk packaging (49 CFR 173.150 (f)(2)). Bulk packaging means packaging other than vessel or barge that has a maximum capacity greater than 450 L (119 gal) for liquid (49 CFR 171.8).

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

BULK SHIPMENTS GREATER THAN 119 GALLONS:

PROPER SHIPPING NAME:	Combustible liquid, n.o.s. (Contains Solvent Naphtha)
HAZARD CLASS NUMBER and DESCRIPTION:	Class 3 Combustible liquid
UN IDENTIFICATION NUMBER:	NA1993
PACKING GROUP:	PGIII
DOT LABEL(S) REQUIRED:	Combustible liquid Class 3
NORTH AMERICAN EMERGENCY RESPONSE	
GUIDEBOOK NUMBER:	128
RQ QUANTITY:	NA
MARINE POLLUTANT:	The components of this product are not designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA):

This product is considered as dangerous goods.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO):

This product is considered as dangerous goods.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):

This product is considered by the United Nations Economic Commission for Europe to be dangerous goods.

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act as follows: None

PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory or are exempted from listing.

OTHER U.S. FEDERAL REGULATIONS: None.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): Ingredients within this product are not on the Proposition 65 Lists.

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: The components of this product are on the DSL Inventory, or are exempted from listing.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This product is a Class B Division 3 Combustible Liquid, Class D2B, Materials causing other toxic effects per WHMIS Controlled Product Regulations.

Safety Data Sheet

Auto Butler Paint Protector GHS SDS

Prepared to U.S., OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives.

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

This product does meet the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives. See Section 2 for Details.

AUSTRALIAN INFORMATION FOR PRODUCT:

The components of this product are listed on the International Chemical Inventory list.

JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS:

The components of this product are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

JAPANESE ENCS INVENTORY: The components of this product are on the ENCS Inventory as indicated in the section on International Chemical Inventories, below.

POISONOUS AND DELETERIOUS SUBSTANCES CONTROL LAW:

No component of this product is listed Specified Poisonous Substance under the Poisonous and Deleterious Substance Control Law.

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:	Listed
Australian Inventory of Chemical Substances (AICS):	Listed
Korean Existing Chemicals List (ECL):	Listed
Japanese Existing National Inventory of Chemical Substances (ENCS):	Listed
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Listed
Swiss Giftliste List of Toxic Substances:	Listed
U.S. TSCA:	Listed

16. OTHER INFORMATION

PREPARED BY: Paul Eigbrett – (GHS MSDS Compliance PLUS)

DATE OF PRINTING: May 31, 2015

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. ChemRite CoPac, Inc. assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, ChemRite CoPac, Inc. assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.